## DESCRIPTION OF PROPOSED WORKS

is to be stored in reservoirs, it should be so stated and the le	cocation of the reservoir should be given with reference to the legal subdivisions.	
nk.		
Estimated cost of works	\$1000.00	•
Estimated time required to d	construct works 5 yrs.	į
Remarks		
	For use of applicant	
/e/F P Wombet		
/s/ E. R. Herbst	, Applicant.	1 :
. 0 10	Ву	;
mpared A. P. J. P.	<del></del>	
is sheet inspected	· 	
	, Engineer.	1
	, Engineer.	
•	OF STATE ENGINEER	!
This is to certify that I	have examined the foregoing application,	
nditions: source and is limite	bject to the following limitations and used subject to all existing rights on the ded to what the well will produce but not	e to
nditions: source and is limite ceed 0.15 c.f.s. If well is	ed to what the well will produce but not flowing, a valve must be installed and	to
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If pe line, near the point of di	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischariversion, and accurate measurements must	ge be
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If pe line, near the point of disput of water placed to benefice st allow for a reasonable low	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischariversion, and accurate measurements must be all use. It is understood that this rivering of the static water level at perm	ge be ght
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If per line, near the point of dispersion of the point of dispersion of the point of a reasonable lowed to be allowed to other ground water cated within an area designate.	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischargersion, and accurate measurements must be all use. It is understood that this rivering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to	ge be ght itt
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If per line, near the point of dispersion of water placed to benefic st allow for a reasonable lower line to other ground water cated within an area designation 4 of the 1939 Ground-Water fore the State retains the	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the discharge in the discharge in the discharge in the discharge in the state measurements must be a seen of the static water level at permodevelopment in the area. This source is ted by the State Engineer pursuant to a ter Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water	ge ght
dditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If per line, near the point of dispersion of the point of dispersion water placed to benefice stallow for a reasonable lower line to other ground water cated within an area designation 4 of the 1939 Ground-Water of the State retains the	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischargersion, and accurate measurements must be installed in the discharger use. It is understood that this rivering of the static water level at permodevelopment in the area. This source is ted by the State Engineer pursuant to atter Act (Chap. 178. State 1939 as amendations are actived to the state of t	ge ght
ditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If per line, near the point of dispersion of the point of dispersion and the point of dispersion and the point of the loss o	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the discharge in the discharge in the discharge in the discharge in the state measurements must be a seen of the static water level at permodevelopment in the area. This source is ted by the State Engineer pursuant to a ter Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water	ge ght
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It per line, near the point of dispersion of the point of dispersion and the point of dispersion and the point of dispersion and the local designation and lo	flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must be installed in the dischart version, and accurate measurements must be accurate measurement of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to ater Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times or shall be limited to the amount	ge ght
ditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If per line, near the point of dispersion of the point of dispersion of the point of dispersion of the local due to other ground water cated within an area designated within an area designated within an area designated at any and all the rein granted at any and all the amount of water to be approping the can be applied to beneficing the can be applied to be appropriately applied to be appropriately applied to be appropriately applied to be applied to be appropriately applied to be appropriately applied to be appli	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischariversion, and accurate measurements must cial use. It is understood that this rivering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to ater Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times shall be limited to the amount al use, and not to exceed 0.15	ge ght
ditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It is per line, near the point of displayed to benefic at allow for a reasonable lowed line to other ground water cated within an area designated to be approper to the line of the line	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must vering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to ater Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times riated shall be limited to the amount al use, and not to exceed 0.15  egin on or before October 10, 1953	gel gbe ght itit
inditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It per line, near the point of dispersion of the point of dispersion of the property of the property of the later of the late	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischariversion, and accurate measurements must be ial use. It is understood that this rivering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to later Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times. The shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1953	gel gbe ght itit
ditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It is per line, near the point of displaying the point of displaying the point of displaying the property of the property of the large designation of the large designation of the large designation of the state retains the property of the large and all the amount of water to be approped to the can be applied to beneficing the per second.  The property of the large designation of the	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must vering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to ater Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times riated shall be limited to the amount al use, and not to exceed 0.15  egin on or before October 10, 1953	gel gbe ght itit
ditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It per line, near the point of displayed to benefic at allow for a reasonable lowest allow for the 1939 Ground-Wasted within an area designated at any and all the amount of water to be approped to be approped to the can be applied to beneficing the feet per second.  The construction work shall be a co	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischariversion, and accurate measurements must be ial use. It is understood that this rivering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to later Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times. The shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1953	gel gbe ght itit
ditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It per line, near the point of disperse of water placed to benefic stallow for a reasonable lowed and the stallow for a reasonable lowed and the stallow for a reasonable lowed at all of the 1939 Ground-Water of the State retains the rein granted at any and all the amount of water to be approping the can be applied to beneficing the feet per second.  The second of the second of the second of commencement of work shall be approping the second of commencement of the second of the seco	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischariversion, and accurate measurements must be ial use. It is understood that this rivering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to later Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times. The shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1953	ge ght
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It per line, near the point of dispersion of the point of dispersion of the property of the large of	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the discharaterion, and accurate measurements must be ial use. It is understood that this rivering of the static water level at perm development in the area. This source is ted by the State Engineer pursuant to ater Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times. The shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1953  sonable diligence and be completed on or the filed before November 10, 1954	ge ght
aditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. It per line, near the point of dispersion of the point of dispersion of the personable lower of the least allow for a reasonable lower of the least and within an area designated within an area designated at any and all the amount of water to be appropanted at any and all the amount of water to be appropanted for the second.  The construction work shall be a construction work shall be a construction of work shall be a co	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must be ial use. It is understood that this rivering of the static water level at perm development in the area. This source it ted by the State Engineer pursuant to a ter Act (Chap. 178, Stats 1939 as amend right to regulate the use of the water times riated shall be limited to the amount al use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1954  al use shall be made on or before	ge ght
nditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. If per line, near the point of dispersion of water placed to benefic stallow for a reasonable lowest allow for a reasonable lowest allow for a reasonable lowest allow for a reasonable lowest of the 1939 Ground-Water to a signatication 4 of the 1939 Ground-Water fore the State retains the rein granted at any and all the samount of water to be appropiated to beneficity of the second.  The can be applied to beneficity of the prosecuted with reasonable prosecuted with reasonable prosecuted with reasonable for completion of work shall be a second of completion of work shall be considered to beneficity of the completion of work shall be considered to beneficity of the completion of work shall be considered to beneficity of the completion of work shall be considered to beneficity of the completion of work shall be considered to beneficity of the completion of water to be completion of the completion of the completion of water to beneficity of the completion of the	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must be installed in the dischart version, and accurate measurements must be acted by the static water level at perm development in the area. This source is ted by the State Engineer pursuant to acter Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times riated shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  sonable diligence and be completed on or be filed before November 10, 1954  all be filed before November 10, 1954  all use shall be made on or before filed before the application of water to beneficial	ge ght
inditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. In personable to personable lower of the personable lower of the personable lower of the least allow for a reasonable lower of the least and water cated within an area designation 4 of the least retains the rein granted at any and all the amount of water to be approping the can be applied to beneficing the personable to be approping the construction work shall be seen of commencement of work shall be for a completion of work shall be core october 10, 1954  The core october 10, 1954  The core of completion of work shall be core to be completed to be	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must be ial use. It is understood that this rivering of the static water level at perm development in the area. This source it ted by the State Engineer pursuant to a ter Act (Chap. 178, Stats 1939 as amend right to regulate the use of the water times riated shall be limited to the amount al use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1954  al use shall be made on or before	ge ght
inditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. A pe line, near the point of dipt of water placed to benefic st allow for a reasonable lowed and the stallow for a reasonable lowed at allow for a reasonable lowed at the stallow for a reasonable lowed at allowed at any and allowere fore the State retains the rein granted at any and allowed amount of water to be approping the can be applied to beneficity of the stall bene	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must be installed in the dischart version, and accurate measurements must be acted by the static water level at perm development in the area. This source is ted by the State Engineer pursuant to acter Act (Chap. 178, Stats 1939 as amend a right to regulate the use of the water times riated shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  sonable diligence and be completed on or be filed before November 10, 1954  all be filed before November 10, 1954  all use shall be made on or before filed before the application of water to beneficial	to ebatt gis e
inditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. A pe line, near the point of dipt of water placed to benefic st allow for a reasonable lowed and the stallow for a reasonable lowed at allow for a reasonable lowed at the stallow for a reasonable lowed at allowed at any and allowere fore the State retains the rein granted at any and allowed amount of water to be approping the can be applied to beneficity of the stall bene	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischart version, and accurate measurements must be ial use. It is understood that this rivering of the static water level at privated by the State Engineer pursuant to ater Act (Chap. 178, Stats 1939 as amend right to regulate the use of the water times riated shall be limited to the amount al use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1953  sonable diligence and be completed on or be filed before November 10, 1954  al use shall be made on or before fithe application of water to beneficial ineer on or before November 10, 1955  ITNESS MY HAND AND SEAL this 10th day.	to ett ()
inditions: source and is limited ceed 0.15 c.f.s. If well is intained to prevent waste. A pe line, near the point of dipt of water placed to benefic st allow for a reasonable lowed and the stallow for a reasonable lowed at allow for a reasonable lowed at allow for a reasonable lowed at a stallow for the least granted at any and all the state retains the rein granted at any and all the amount of water to be approping to the approping amount of water to be approping to the stall be seen to be approped to a stall be seen to be approped to the stall be approped to a stall be approped to b	ed to what the well will produce but not flowing, a valve must be installed and a meter must be installed in the dischartiversion, and accurate measurements must be installed in the dischartiversion, and accurate measurements must be in the static water level at perm development in the area. This source it ted by the State Engineer pursuant to a ter Act (Chap. 178, Stats 1939 as amend at right to regulate the use of the water times rilated shall be limited to the amount all use, and not to exceed 0.15  egin on or before October 10, 1953  all be filed before November 10, 1953  sonable diligence and be completed on or be filed before November 10, 1954  all use shall be made on or before filed before November 10, 1954  all use shall be made on or before filed before November 10, 1955  ITNESS MY HAND AND SEAL this 10th day.	to ett ()